

### AC+DC combo Charge Socket

Power Contact 12mm/6mm, Ground Contact 6mm, and Signal Contact 3mm

Part-No.: CS250+32

#### DC Performance(直流插座性能参数):

- Current capacity(额定电流): 80/125/200/250A
- Voltage(额定电压): DC 750V
- Temperature range(温度区间): -30°C to +50°C
- Sealing protection(密封等级): IP54 (插合前)
- Sealing protection(密封等级): IP55 (插合后)
- Mating force (插拔力): <140N
- Locking Force (锁止力): >200N
- Cycle time (寿命): >10000次
- Microswitch (微动开关): 可选
- temperature monitor (温度监控): NTC10K

#### AC Performance(交流插座性能参数):

- Current capacity(额定电流): 10/16/32/63A
- Voltage(额定电压): AC 250V
- Temperature range(温度区间): -30°C to +50°C
- Sealing protection(密封等级): IP54 (插合前)
- Sealing protection(密封等级): IP55 (插合后)
- Mating force (插拔力): <100N
- Locking Force (锁止力): >200N
- Cycle time (寿命): >10000次
- temperature monitor (温度监控): NTC10K

#### Performance(LED灯性能参数):

- Option (可根据客户要求定制灯色和控制逻辑)



#### Construction:

- ➔ Housing material: PA66-GF V0
- ➔ Terminal material: Copper, BeCu, Ag plating

#### Dimensional characteristics:

